



Eco-Friendly



Non-Toxic

ACRYLIC EMULSION

SINOGRACE

The Chemical Company

Architectural Coatings

PA-239 Pure Acrylic Emulsion

DESCRIPTION

Pure acrylic emulsion is designed for high grade exterior wall latex paint. Excellent water resistant, weatherability, outstanding yellowing&aging resistance.

TYPE

Pure acrylic polymer dispersion

KEY

- High gloss
- Fine particle size
- High hardness and excellent rub resistance
- Good resistance to water, alkali, acid rain and stain
- Outstanding yellowing&aging resistance and excellent weatherability

FEATURES**TYPICAL**

Appearance Milky white liquid

pH 7-9

Solid content 48±1%

Glass Transition Temperature 25°C

Viscosity (25°C) 100-500cP

PROPERTIES

Freeze-thaw stability Yes

Ca²⁺ stability 5%CaCl₂: emulsion =1:3, 48h, No Flocculation, No Stratification. Pass

APPLICATION

- Interior and exterior wall paint

STORAGE**AND****HANDLING**

- Available in 200 kg/ barrel or 25 kg/ barrel
- Store products in tightly closed original containers at 5-40°C
- Shelf life: 9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589