



## Water based Adhesive

# SA-238PP/PE Water based pressure adhesive for Aluminized

#### PP/PE films

DES	CDI	TATA

SA-238PP/PE is an adhesive specially designed for reverse gravure coaters, for the production of general purpose filmic labels (PP, PE, etc.) or other Aluminized pressure sensitive materials.

**TYPE** 

Acrylic ester aqueous dispersion

### KEY

- Eco friendly
- High and low temperature resistant

### **FEATURES**

- Excellent balance of tack and shear
- Good adhesion to aluminized surface, no blistering

# **TYPICAL**

## **PROPERTIES**

Appearance	Milky white liquid
pH	6.0-8.0
Solid content	54±1%
Type of emulsion	Anionic
Viscosity (25°C)	17S-21S
<b>Density (20℃)</b>	1.02 g/cm3
Surface of the film	Tacky, clear

#### **APPLICATION**

- Suitable for PP, PE, and other aluminized film materials
- Adhesion of advertising materials etc.

#### **STORAGE**

• Available in 200 kg/ barrel or 1000 kg/ barrel (IBC)

AND

• Store products in tightly closed original containers at 5-35°C

• Shelf life: 6-9 months from delivery date

### **HANDLING**

• According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd. Add.: Hefei city, Anhui province, China

Tel: +86-0551-63459511 Mob: +86 15755193346

Email: <a href="mailto:sales@sinogracechem.com">sales@sinogracechem.com</a> Web: <a href="mailto:www.sinogracechem.com">www.sinogracechem.com</a>