



# Water based Adhesive

## SA-P224 Water based glue for metal colored stone roof tile

DES	CR.	<b>IP</b> 7	$\Gamma T$	ON

It is composed of special crosslinking monomer polymerization. Apply to stick the color sand on the galvanized steel plate. Excellent adhesive force, water resistant and weatherability

ТҮРЕ	Self-crosslinking fluoro acrylic copolymer dispersion		
	<ul> <li>Non toxic</li> </ul>		
KEY	<ul> <li>Excellent adhesive force</li> </ul>		
<b>FEATURES</b>	<ul> <li>Good leveling property</li> </ul>		
	<ul> <li>Excellent water resistant and weatherability</li> </ul>		

# TYPICAL PROPERTIES

Appearance	Milky white liquid
рН	8.0-9.5
$\operatorname{Tg}\left( {\Bbb C} ight)$	13
Solid content	50±1%
Charge	Anionic
Viscosity (25°C)	1500-3000cP
Mechanical Stability	Very good

#### **APPLICATION**

Metal colored stone tile etc.

# HOW TO USE

- Step-1: Clean the metal plate surface. Then spray the glue 200~300g/m<sup>2</sup> on the metal surface (According to the particle size of color sand to adjust the spray glue quantity.)
- Step-2: Put the color sand particle on the glue uniformly. Dry it under  $80\sim120^{\circ}$  for  $20\sim30$  min.
- Step-3: Spray the surface glue SA-P224 and dry it under  $80 \sim 120 ^{\circ}\text{C}$  for  $20 \sim 30 \text{ min}$ .

### STORAGE AND HANDLING

- Available in 200 kg/ barrel or 1000 kg/ barrel (IBC)
- Store products in tightly closed original containers at 5-35°C
- Shelf life: 6-9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd. Add.: Hefei city, Anhui province, China

Tel: +86-0551-63459511 Mob: +86 15855525589

Email: <a href="mailto:sales@sinogracechem.com">sales@sinogracechem.com</a> Web: <a href="mailto:www.sinogracechem.com">www.sinogracechem.com</a>