



Eco-Friendly



Non-Toxic

ACRYLIC EMULSION

SINOGRACE

The Chemical Company

Floor care

SA-A10 Anti - static floor coating

DESCRIPTION

SA-A10 anti-static floor coating is a kind of floor brightener. It is prepared by scientific formula and strict process with acrylic polymer emulsion and additives. It has fast drying speed, high surface brightness, In addition to the effect of ordinary floor polish, anti-static floor coating also has static dissipative function.

TYPE

Modified Acrylic copolymer dispersion

KEY

FEATURES

- Leveling: Freely spread on any floor material
- Fast drying: no more than 30 minutes (room temperature)
- High gloss: moderate gloss before polishing, better gloss after polishing
- Wear resistance: it is not easy to leave marks
- Anti-scratch: sufficient hardness and toughness
- Anti-pollution: no dust, easy to clean and maintain
- Anti-slip property: it will not slip when stepped on
- Easy to remove: old wax layer is easy to remove

TYPICAL

PROPERTIES

Appearance	Milky white liquid
PH	7-8
Solid content	20±1%
Surface resistance	10 ⁵ -10 ⁸ ohm
Volume Resistance	10 ⁵ -10 ⁸ ohm
Electrification voltage	<70V
Cover area	30-40 m ² / kg(one layer)

APPLICATION

- Wood floor
- Concrete floor
- Epoxy floor
- Plastic compound floor
- PVC and vinyl surface

STORAGE

AND

HANDLING

- Available in 200 kg/ barrel or 25 kg/ barrel
- Store products in tightly closed original containers at 5-40°C
- Shelf life: 9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15755193346